



Our HeliQ lift is a modern, discreet stationary lift that can be installed in a rail system or freestanding gantry system. It is a solution suitable for both acute care facilities, nursing homes or home care environments.

Contemporary Design

The HeliQ stationary overhead lift features a modern, discreet look that easily fits into any environment. Its small size ensures ease of use in either institutional or home care applications. The lift comes in three different models with three different weight capacities. It allows optimal patient comfort with 2-point or 4-point hanger bars in different lengths to suit virtually any patient.

Lift Intelligence

The HeliQ features an advanced technology platform that allows tracking of lift usage and visualization of collected data. This integrated lift intelligence allows data to be retrieved using our Data and Service

Application on a tablet or computer. Detailed information can be viewed directly in the application or exported to other media for additional analysis.

Power Traverse and In-Rail Charging

The HeliQ lifts have an option to be connected to a power traverse, enabling lateral motorized movement, including the possibility of passing curtain gaps in rails. The HeliQ power traverse has dual speed, high water protection (IPX4) and a 300kg/661lb safe working load. The HeliQ can also work with in-rail charging, allowing the lift to be ready for use at all times.

HUMAN CARE SWEDEN (HQ)

Årstaängsvägen 21B
117 43 Stockholm
Phone: +46 8 665 35 00
Fax: +46 8 665 35 10
info.se@humancaregroup.com

HUMAN CARE AUSTRALIA

Unit 4, 49 Bertie Street
Port Melbourne, VIC 3207
Phone: +61 1300 132 736
Fax: +61 (03) 9645 4954
info.au@humancaregroup.com

HUMAN CARE CANADA

10-155 Colonnade Road
Ottawa, ON K2E 7K1
Phone: +613.723.6734
Fax: +613.723.1058
info.ca@humancaregroup.com

HUMAN CARE NEDERLAND

Elspeterweg 124
8076 PA Vierhouten
Phone: +31 577 412 171
Fax: +31 577 412 170
info.nl@humancaregroup.com

HUMAN CARE UNITED STATES

8006 Cameron Road, Suite K
Austin, TX 78754
Phone: +512.476.7199
Fax: +512.476.7190
info.us@humancaregroup.com

Accessories



Hanger bar
Three widths. Order separately. Part no.: 72754 [35cm/13.8"]
72755 [45cm/17.7"]
72757 [60cm/23.6"]



Powered spreader bar
For use with clip slings in hospital or other care environments. Part no.: Small 92441, Medium 92442, Large 92443




Handset
Input for charging and USB interface. IPX5 water protection rating. Part no.: 71458 [71459 for Power Traverse lift]



Upholstered Cover
Protects user from hanger bar impact. Hanger bar sold separately. Part no. 50866



Lift charger
Charger with holder. Easily attaches to wall. Part no. 50899-US



Gates and Turntables
Offering additional lift transfer options on rails. Part no. 55721 [Gate], 91884 [Turntable]



4-point suspension
Enables 4-point lifting. Part no.: 70800



Distance Strap
Reinforced nylon thread and metal hooks. Extend lift strap up to 100cm/39.3". Part no. 20124-xx [specify length]




Secondary Control
Secondary control panel on back of lift for emergency stop function. Integrated feature.



Power traverse
Enables lateral motorized movement. Order with lift.



Scale
Medical grade scale. Max. capacity 320kg/705.5lb. ISO and EN compliant. Part no.: 50348, 50345 [Canada]



Insights
Lift intelligence that facilitates cloud based storage of collected data. Integrated feature.

Technical Specifications

Description	HeliQ 150	HeliQ 220	HeliQ 300
Part Number	55100-[Country Code]	55110-[Country Code]	55120-[Country Code]
Part Number (Power Traverse)	55130-[Country Code]	55140-[Country Code]	55150-[Country Code]
Part Number (Hanger Bar)	72754, 72755, 75757	72754, 72755, 75757	72754, 72755, 75757
Dimensions (W x H x L)	23.5cm x 23.5cm x 14cm 9.2" x 9.2" x 5.5"		
Safe Working Load	150kg/330lb	220kg/484lb	300kg/661lb
Product Weight (Lift)	7.6kg / 16.7lb		
Product Weight (Hanger Bar)	0.9kg/2.1lb [72754], 1.1kg/2.5lb [72755], 1.4kg/3.1lb [72757]		
Battery	2.3Ah, 2x12V		
Battery Charger	Input: 100-240V, AC 50-60 Hz Output: 27.8V, 0.8A DC		
IP Class	Lift: IPX4 Hand Control: IPX5		
Lifting Distance and Speed	Distance: 208cm/81.9" Speed: 1.8m/min - 3m/min — 70"/min - 118"/min		
Approvals	ROHS-2 approved, Tested and approved according to ISO 10535:2006 ETL Listed		
Emergency Lowering	Electronic and Mechanical		

Country Codes: AU-Australia, GB-Great Britan, EU-Europe, JP-Japan, NA-North America

This product is manufactured in accordance with all relevant ISO standards.



Learn more about this product



Follow Us on Social Media



facebook.com/humancarecda



instagram.com/humancaregroup



linkedin.com/company/human-care-ab



pinterest.com/humancaregroup



youtube.com/channel/UC7fyjNH3zTjRxOP1IDf2Da0